

beeFlex™ 7 Way Plug Coil Assemblies



ABS COIL ASSEMBLIES - GREEN

4/12, 2/10, 1/8 gauge SAE J2394 Cable

- Recommended for all ABS application
- Meets TMC R.P. 137
- Superb Coil Memory
- Exceptional abrasion resistance
- Extreme resistance to UV light, Commonly used Chemicals, Gasoline, Oils, Grease and Diesel
- Temperature range -85°F to +185°F
- SAE J560b Plugs with Floating brass pins



Working Length	Leads	Catalog No. With Metal Plug w/Spring Guard	Catalog No. With Plastic Weather Guard Plug
12'	12"	19822	19822PL
15'	12"	19872	19872PL
15'	1 X 12" – 1 X 40"	19875	19875PL
15'	1 X 12" – 1 X 48"	19877	19877PL
15'	1 X 12" – 1 X 72"	19876	19876PL
20'	12"	19852	19852PL

Consult factory for other sizes



ISO COIL ASSEMBLIES - YELLOW

4/12, 2/10, 1/8 gauge Cable

- Recommended for trailers with ISO Sockets
- Made with same ABS Cable construction
- Meets TMC R.P. 137
- Superb Coil Memory
- Exceptional abrasion resistance
- Extreme resistance to UV light, Commonly used Chemicals, Gasoline, Oils, Grease and Diesel
- Temperature range -85°F to +185°F
- ISO 3731 Plugs with inverted ground pin**

Working Length	Leads	Catalog No. With Metal Plug w/Spring Guard
12'	12"	19922
15'	12"	19972
15'	1 X 12" – 1 X 48"	19977
15'	1 X 12" – 1 X 72"	19976

Consult factory for other sizes

Note: All coils are listed as working length. Working length is determined at 25 pounds of direct pull pressure. Actual wire lengths are longer.