


beeFlex™ Starter Cable

-Meets SAE J1127 Type SGT Specifications


- Annealed soft Rope Stranded Copper for Flexibility
- Flexible abrasion resistance PVC Insulation
- Temperature rating of 80°C (176°F)
- 50 Volts or less



Gauge	Color	Stranding	25' Box #	50' Box #	100' Box #	250' Spool #	500' Spool #	O.D.
6	Red	133	206-5T	206-5P	206-5C	206-5L	206-5X	.341
6	Black	133	206-7T	206-7P	206-7C	206-7L	206-7X	.341
4	Red	133	204-5T	204-5P	204-5C	204-5L	204-5X	.352
4	Black	133	204-7T	204-7P	204-7C	204-7L	204-7X	.352
2	Red	196	202-5T	202-5P	202-5C	202-5L	202-5X	.445
2	Black	196	202-7T	202-7P	202-7C	202-7L	202-7X	.445
1	Red	245	201-5T	201-5P	201-5C	201-5L	201-5X	.475
1	Black	245	201-7T	201-7P	201-7C	201-7L	201-7X	.475
1/0	Red	315	210-5T	210-5P	210-5C	210-5L	210-5X	.505
1/0	Black	315	210-7T	210-7P	210-7C	210-7L	210-7X	.505
2/0	Red	406	220-5T	220-5P	220-5C	220-5L	220-5X	.565
2/0	Black	406	220-7T	220-7P	220-7C	220-7L	220-7X	.565
3/0	Red	525	230-5T	230-5P	230-5C	230-5L	230-5X	.675
3/0	Black	525	230-7T	230-7P	230-7C	230-7L	230-7X	.675
4/0	Red	588	240-5T	240-5P	240-5C	240-5L	240-5X	.750
4/0	Black	588	240-7T	240-7P	240-7C	240-7L	240-7X	.750

600 Volts Class K-Neoprene Welding Cable

- Highly Flexible Soft-drawn Copper
- Flame, oil, abrasion, tear and grease resistance
- Temperature rating of -50°C to 105°C (-58°F to 221°F)



Gauge	Color	Stranding	25' Box #	50' Box #	100' Box #	250' Spool #	500' Spool #	O.D.
6	Red	266	406-5T	406-5P	406-5C	406-5L	406-5X	.340
6	Black	266	406-7T	406-7P	406-7C	406-7L	406-7X	.340
4	Red	420	404-5T	404-5P	404-5C	404-5L	404-5X	.380
4	Black	420	404-7T	404-7P	404-7C	404-7L	404-7X	.380
2	Red	665	402-5T	402-5P	402-5C	402-5L	402-5X	.440
2	Black	665	402-7T	402-7P	402-7C	402-7L	402-7X	.440
1	Red	836	401-5T	401-5P	401-5C	401-5L	401-5X	.530
1	Black	836	401-7T	401-7P	401-7C	401-7L	401-7X	.530
1/0	Red	1064	410-5T	410-5P	410-5C	410-5L	410-5X	.580
1/0	Black	1064	410-7T	410-7P	410-7C	410-7L	410-7X	.580
2/0	Red	1323	420-5T	420-5P	420-5C	420-5L	420-5X	.615
2/0	Black	1323	420-7T	420-7P	420-7C	420-7L	420-7X	.615
3/0	Red	1666	430-5T	430-5P	430-5C	430-5L	430-5X	.690
3/0	Black	1666	430-7T	430-7P	430-7C	430-7L	430-7X	.690
4/0	Red	2035	440-5T	440-5P	440-5C	440-5L	440-5X	.740
4/0	Black	2035	440-7T	440-7P	440-7C	440-7L	440-7X	.740

Excellence Through Quality...