

# SXL Cross-link Primary Wire

## -Meets SAE J1128 Specifications

- Recommended for Trucks, Tractors and Cars engine compartment where higher heat resistance is required
- Stranded annealed soft copper
- Temperature rating of -51°C to 125°C (-59°F to 257°F)
- Straight line, Spiral or Hash mark Striping available
- Printing available



	Color	100' Spool #	250' Spool #	500' Spool #	1000' Spool #	3000' Spool #
10 Gauge	Blue	310-1C	310-1L	310-1X	310-1M	310-1-3M
	White	310-2C	310-2L	310-2X	310-2M	310-2-3M
	Green	310-3C	310-3L	310-3X	310-3M	310-3-3M
19/23 Stranding	Yellow	310-4C	310-4L	310-4X	310-4M	310-4-3M
	Red	310-5C	310-5L	310-5X	310-5M	310-5-3M
	Brown	310-6C	310-6L	310-6X	310-6M	310-6-3M
.193 O.D.	Black	310-7C	310-7L	310-7X	310-7M	310-7-3M
	Orange	310-8C	310-8L	310-8X	310-8M	310-8-3M

	Color	100' Spool #	250' Spool #	500' Spool #	1000' Spool #	4000' Spool #
12 Gauge	Blue	312-1C	312-1L	312-1X	312-1M	312-1-4M
	White	312-2C	312-2L	312-2X	312-2M	312-2-4M
	Green	312-3C	312-3L	312-3X	312-3M	312-3-4M
19/25 Stranding	Yellow	312-4C	312-4L	312-4X	312-4M	312-4-4M
	Red	312-5C	312-5L	312-5X	312-5M	312-5-4M
	Brown	312-6C	312-6L	312-6X	312-6M	312-6-4M
.163 O.D.	Black	312-7C	312-7L	312-7X	312-7M	312-7-4M
	Orange	312-8C	312-8L	312-8X	312-8M	312-8-4M

	Color	100' Spool #	250' Spool #	500' Spool #	1000' Spool #	5000' Spool #
14 Gauge	Blue	314-1C	314-1L	314-1X	314-1M	314-1E
	White	314-2C	314-2L	314-2X	314-2M	314-2E
	Green	314-3C	314-3L	314-3X	314-3M	314-3E
19/27 Stranding	Yellow	314-4C	314-4L	314-4X	314-4M	314-4E
	Red	314-5C	314-5L	314-5X	314-5M	314-5E
	Brown	314-6C	314-6L	314-6X	314-6M	314-6E
.141 O.D.	Black	314-7C	314-7L	314-7X	314-7M	314-7E
	Orange	314-8C	314-8L	314-8X	314-8M	314-8E

	Color	100' Spool #	250' Spool #	500' Spool #	1000' Spool #	8000' Spool #
16 Gauge	Blue	316-1C	316-1L	316-1X	316-1M	316-1-8M
	White	316-2C	316-2L	316-2X	316-2M	316-2-8M
	Green	316-3C	316-3L	316-3X	316-3M	316-3-8M
19/29 Stranding	Yellow	316-4C	316-4L	316-4X	316-4M	316-4-8M
	Red	316-5C	316-5L	316-5X	316-5M	316-5-8M
	Brown	316-6C	316-6L	316-6X	316-6M	316-6-8M
.120 O.D.	Black	316-7C	316-7L	316-7X	316-7M	316-7-8M
	Orange	316-8C	316-8L	316-8X	316-8M	316-8-8M