

beeFlex™ Bonded Parallel Primary Wire

- Meets SAE J1128 Specifications
- Used in RVs and Utility trailers
- 50 Volts or less
- PVC Insulation 80°C (176°F)



Two Conductors (Color: Blk, Red)

Gauge/ #Cond.	Stranding	100' Box #	250' Spool #	500' Spool #	1000' Spool #	O.D.
14/2	19/27	10142C	10142L	10142X	10142M	.119 X .240
16/2	19/29	10162C	10162L	10162X	10162M	.104 X .210
18/2	16/30	10182C	10182L	10182X	10182M	.092 X .186



Three Conductor (Color: Yel, Brn, Grn)

Gauge/ #Cond.	Stranding	100' Box #	250' Spool #	500' Spool #	1000' Spool #	O.D.
12/3	19/25	10123C	10123L	10123X	10123M	.143 X .432
14/3	19/27	10143C	10143L	10143X	10143M	.119 X .358
16/3	19/29	10163C	10163L	10163X	10163M	.104 X .312
18/3	16/30	10183C	10183L	10183X	10183M	.092 X .279



Four Conductor (Color: Yel, Brn, Grn, Wht)

Gauge/ #Cond.	Stranding	100' Box #	250' Spool #	500' Spool #	1000' Spool #	O.D.
12/4	19/25	10124C	10124L	10124X	10124M	.143 X .575
14/4	19/27	10144C	10144L	10144X	10144M	.199 X .480
16/4	19/29	10164C	10164L	10164X	10164M	.104 X .416



Five Conductor (Color: Yel, Brn, Grn, Wht, Red)

Gauge/ #Cond.	Stranding	100' Box #	250' Spool #	500' Spool #	1000' Spool #	O.D.
14/5	19/27	10145C	10145L	10145X	10145M	.119 X .600

beeFlex™ Stereo Speaker Wire

- One bright Tinned and One Bare soft annealed stranded Copper wire
- Smooth Clear .030 wall PVC Insulation
- Packaged on Spool
- Optional 1,000 ft. bee-Quick easy Pull box available



Gauge/ #Cond.	Stranding	100' Spool #	1000' Spool #	O.D.
22/2	7/30	61720C	61720M	.090 X .185
18/2	16/30	61730C	61730M	.105 X .214
16/2	26/30	61800C	61800M	.121 X .247
14/2	41/30	61805C	61805M	.137 X .279
12/2	65/30	61806C	61806M	.154 X .313

Excellence Through Quality...